lumen™
EFFICIENT DESIGN INC.

LED FIXTURES

In-Stock Mini-Catalog

Area · Wall Packs · Flood · Panels · Troffers
Strips · Vapor Tight · High Bay · Emergency

November 2026



Lumen Efficient Design Inc.
lumenefficientdesign.ca
Contact us for pricing and quantities.

LED FIXTURES — IN STOCK

Lumen Efficient Design Inc. · lumenefficientdesign.ca

Area lights, wall packs, floods, emergency, vanity, flush mounts, pot lights, architectural linear, wraps, panels, troffers, strips, vapor tight and high bays — ready to ship. Contact us for pricing and quantities.

Wattage & CCT — 840 = 4000K, 850 = 5000K. 3CCT / 8CCT3 / CCT3 / C3 = selectable CCT (ranges vary by family; see Notes). 5CCT = 2700/3000/3500/4000/5000K on LEDI pots and flush mounts. Multi-watt listings (e.g. 15/24/30/40) are selectable wattage.

Voltage & options — 120-347V is typical Canadian commercial multi-volt. PHO = photocell included. Z10 = Z10 control receptacle. SPCDNA = sensor port. Type III / 3S / T3 = Type III distribution.

Finishes — BZ = bronze, BK = black, DB = dark bronze, W = white. EEL = Energy Efficient Lighting. LEDI = Lumen Efficient Design.

EXTERIOR

1 Area Lights (7)



Part Number / Description	Brand	Watts	CCT	Voltage	Notes
FXCAL100/840/BZ/3S/347 Area Light	NaturaLED	100	4000K	120-347V	Type III, bronze
FXCAL100/850/BZ/3S/347 100W Area Light	NaturaLED	100	5000K	120-347V	Type III, bronze
LED-FXCAL150/840/BZ/3S/347 Area Light	NaturaLED	150	4000K	120-347V	Type III, bronze
LED-FXCAL150/850/BZ/3S/347 Area Light	NaturaLED	150	5000K	120-347V	Type III, bronze
FXCAL300/840/BZ/3S/347 Area Light	NaturaLED	300	4000K	120-347V	Type III, bronze
FXCAL300/850/BZ/3S/480 277/480 Area Light	NaturaLED	300	5000K	277-480V	Type III, bronze
FXCAL300/T3/C3/BZ-Z10 120-277V Area Light	NaturaLED	300	3CCT	120-277V	3CCT, Z10, Type III, bronze

2 Wall Packs (14)



Part Number / Description	Brand	Type	Watts	CCT	Voltage	Notes
LED-FXTWP38/40K/BZ-PHO Wallpack	NaturaLED	Standard	38	4000K	120-277V	photocell, bronze
LED-FXTWP38/40K/BZ/347-PHO Wallpack	NaturaLED	Standard	38	4000K	120-347V	photocell, bronze
FXTWP38/50K/BZ-PHO Wallpack	NaturaLED	Standard	38	5000K	120-277V	photocell, bronze
LED-FXTWP38/50K/BZ/347-PHO Wallpack	NaturaLED	Standard	38	5000K	120-347V	photocell, bronze
WP3226-40W40K-120-347VNS1-10V WALL PACK	EEL	Standard	40	4000K	120-347V	1-10V dim

Part Number / Description	Brand	Type	Watts	CCT	Voltage	Notes
WP3256-40W50K-120-347VVN1S-10V WALL PACK	EEL	Standard	40	5000K	120-347V	1-10V dim
FXSWP45SW/8CCT3/BK/347/PHO Slim Wall Pack	NaturaLED	Slim	15/28/45	3CCT	120-347V	selectable wattage, 3CCT, photocell, black
LED-FXTWP60/40K/BZ/347-PHO Wallpack	NaturaLED	Standard	60	4000K	120-347V	photocell, bronze
WP3326-60W40K-120-347VNS1-10V WALL PACK	EEL	Standard	60	4000K	120-347V	1-10V dim
LED-FXTWP60/50K/BZ/347-PHO Wallpack	NaturaLED	Standard	60	5000K	120-347V	photocell, bronze
LED-FXCWP80/40K/BZ Full Cutoff Wallpack	NaturaLED	Full Cutoff	80	4000K	120-277V	bronze
WP3526-90W40K-120-347VNS1-10V WALL PACK	EEL	Standard	90	4000K	120-347V	1-10V dim
LED-FXTWP100SW/CCT3/BZ/347-PHO Wallpack	NaturaLED	Standard	60/80/100	3CCT	120-347V	selectable wattage, 3CCT, photocell, bronze
LED-FXTWP120/50K/DB Wallpack	NaturaLED	Standard	120	5000K	—	dark bronze

3 Floodlights (3)



Part Number / Description	Brand	Watts	CCT	Voltage	Notes
LED-FXFDL28/40K/BK Floodlight	NaturaLED	28	4000K	—	black
SNC-FL06-30WCTA1-50-YM	Lumen (LEDI)	30	—	—	YM mount
SNC-FL06-50WCT1A1-50-FM	Lumen (LEDI)	50	—	—	FM mount

INTERIOR

4 Emergency & Exit (4)



Part Number / Description	Brand	Watts	CCT	Voltage	Notes
RHL-24V1 SINGLE REMOTE HEAD	Lumen (LEDI)	—	—	24V	single remote head
RHL-24V2 DOUBLE REMOTE HEAD	Lumen (LEDI)	—	—	24V	double remote head
ELR-RC TWIN HEAD EMERGENCY LIGHT	Lumen (LEDI)	—	—	—	twin-head emergency unit
RMP-RC RUNNING MAN EXIT SIGN	Lumen (LEDI)	—	—	—	running-man exit sign

5 Vanity / Décor (1)



Part Number / Description	Brand	Watts	CCT	Voltage	Notes
TP-VL01-E1-G2-DIM-AL 24" VANITY 120V 3K 1600LM	Lumen (LEDI)	—	3000K	120V	dimmable, 24 in, 1,600 lm

6 Flush Mount (2)



Part Number / Description	Brand	Watts	CCT	Voltage	Notes
LEDI-PR305M-CL02-20W120-5CCT/S	Lumen (LEDI)	20	5CCT	120V	5CCT 2700/3000/3500/4000/5000K, 12 in, nickel, 1,400 lm, TRIAC dim
LEDI-PR355M-CL02-26W120-5CCT/S	Lumen (LEDI)	26	5CCT	120V	5CCT 2700/3000/3500/4000/5000K, 14 in, nickel, 1,820 lm, TRIAC dim

7 Recessed / Pot Lights (2)



Part Number / Description	Brand	Watts	CCT	Voltage	Notes
PVDL-GEN02-8WE-01 4' 8W 5CCT Pot Light	Lumen (LEDI)	8	5CCT	120V	5CCT 2700/3000/3500/4000/5000K, 4 in, TRIAC dim
PVDL-GEN02-12WG-01 6' 12W 5CCT Pot Light	Lumen (LEDI)	12	5CCT	120V	5CCT 2700/3000/3500/4000/5000K, 6 in, TRIAC dim

8 Architectural Linear (4)



Part Number / Description	Brand	Watts	CCT	Voltage	Notes
LI-J1200-347V-050D-PPCDNS-W 4ft Linear Fixture	Lumen (LEDI)	50	3CCT	120-347V	3CCT 3000/4000/5000K, white, 4 ft
LI-J1200-347V-050D-PPCDNS-B 4ft Linear Fixture	Lumen (LEDI)	50	3CCT	120-347V	3CCT 3000/4000/5000K, black, 4 ft
LI-J2400-347V-100D-PPCDNS-W 8ft WH Linear	Lumen (LEDI)	100	3CCT	120-347V	3CCT 3000/4000/5000K, white, 8 ft
LEDI-LI-J2400-347V-100D-PPCDNS-B 8ft Black Linear	Lumen (LEDI)	100	3CCT	120-347V	3CCT 3000/4000/5000K, black, 8 ft

9 Surface Wrap (1)



Part Number / Description	Brand	Watts	CCT	Voltage	Notes
N-LS8-4FT-40W-140-D-FL-CT-FA Wrap C/W Sensor Inst.	Lumen (LEDI)	15/24/30/40	3CCT	120-347V	3CCT 3500/4000/5000K, selectable wattage, 4 ft, sensor installed, 0-10V dim

10 Flat Panels (6)



Part Number / Description	Brand	Watts	CCT	Voltage	Notes
PL-14-BL-347V-40D-PPCDN	Lumen (LEDI)	40	3CCT	120-347V	3CCT 3500/4000/5000K, 1×4
PL-14-BL-347V-40D-SPCDNA 1X4 Panel W/Sen Port	Lumen (LEDI)	40	3CCT	120-347V	3CCT 3500/4000/5000K, sensor port, 1×4
PL-22-BL-347V-40D-PPCDN	Lumen (LEDI)	40	3CCT	120-347V	3CCT 3500/4000/5000K, 2×2
PL-22-BL-347V-40D-SPCDNA 2X2 Panel c/w Sensor Port	Lumen (LEDI)	40	3CCT	120-347V	3CCT 3500/4000/5000K, sensor port, 2×2
PL-24-BL-347V-50D-PPCDN	Lumen (LEDI)	50	3CCT	120-347V	3CCT 3500/4000/5000K, 2×4
PL-24-BL-347V-50D-SPCDNA 2X4 Panel W/Sen Port	Lumen (LEDI)	50	3CCT	120-347V	3CCT 3500/4000/5000K, sensor port, 2×4

11 Troffers (6)



Part Number / Description	Brand	Watts	CCT	Voltage	Notes
PL-14-TF-347V-40D-PPCDN	Lumen (LEDI)	40	—	120-347V	1×4
PL-14-TFC-347V-40D-PPCDN Curved Troffer	Lumen (LEDI)	40	—	120-347V	1×4, curved
PL-22-TF-347V-40D-PPCDN Center Basket Troffer	Lumen (LEDI)	40	—	120-347V	2×2, center basket
PL-22-TFC-347V-40D-PPCDN Curved Indirect Troffer	Lumen (LEDI)	40	—	120-347V	2×2, curved indirect
PL-24-TF-347V-50D-PPCDN TROFFER	Lumen (LEDI)	50	—	120-347V	2×4
PL-24-TFC-347V-50D-PPCDN Curved Troffer	Lumen (LEDI)	50	—	120-347V	2×4, curved

12 Industrial Strips (5)



Part Number / Description	Brand	Watts	CCT	Voltage	Notes
STD-024-AW-NW-01T - 2 foot, 4000K, 120-277V	Lumen (LEDI)	—	4000K	120-277V	2 ft
STD-024-AW-NW-03T 4-FOOT 4000K 120-277V	Lumen (LEDI)	—	4000K	120-277V	4 ft
STD-036-AW-NW-01T - 48 Foot, 4000K, 120-277V	Lumen (LEDI)	—	4000K	120-277V	—
N-LS2.5-4FT-40W-140-D-FL-CT-FA 4ft Low Bay	Lumen (LEDI)	15/24/30/40	3CCT	120-347V	3CCT 3500/4000/5000K, selectable wattage, 4 ft
N-LS2.5-8FT-80W-140-D-FL-CT-FA 8ft Low Bay	Lumen (LEDI)	45/60/70/80	3CCT	120-347V	3CCT 3500/4000/5000K, selectable wattage, 8 ft

13 Vapor Tight (2)



Part Number / Description	Brand	Watts	CCT	Voltage	Notes
N-VTR-4FT-50W-140-G-FL-CT-FA-EMXX 4ft Low Bay	Lumen (LEDI)	20/35/40/50	3CCT	120-347V	3CCT 3500/4000/5000K, selectable wattage, 4 ft, IP65
N-VTR-8FT-80W-140-G-FL-CT-FA-EMXX 8ft High Bay	Lumen (LEDI)	45/60/70/80	3CCT	120-347V	3CCT 3500/4000/5000K, selectable wattage, 8 ft, IP65

14 UFO High Bays (2)



Part Number / Description	Brand	Watts	CCT	Voltage	Notes
HB08-200M-CS-3CCT UFO High Bay 120-347V 3CCT	Lumen (LEDI)	200	3CCT	120-347V	3CCT
HB08-300M-CS-3CCT UFO High Bay 120-347V 3CCT	Lumen (LEDI)	300	3CCT	120-347V	3CCT

15 Linear High Bays (3)



Part Number / Description	Brand	Watts	CCT	Voltage	Notes
N-HBL-12-125W-850-F-FA 95/105/115/125W Linear	Lumen (LEDI)	95/105/115/125	5000K	120-347V	selectable wattage, 0-10V dim
N-HBL-14-210W-850-F-FA 150/170/190/210W Linear	Lumen (LEDI)	150/170/190/210	5000K	120-347V	selectable wattage, 0-10V dim
N-HBL-14-320W-850-F-FA 260/280/300/320W Linear	Lumen (LEDI)	260/280/300/320	5000K	120-347V	selectable wattage, 0-10V dim