



UL US LISTED
UG-TR/D1/120



UG-TR/D1/240



UL US LISTED
UG-TR/D2/120

Digital Timers: 1 Year Warranty

Item Code	Description	Volts	Amps	Hz	Watts	Length	Width	Height	Weight	CS/QTY
UG-TR/D1/120	Digital Timer 120V, Single outlet	115	15	60	1725	2 ⁷ / ₈ "	3 ¹ / ₂ "	4 ⁵ / ₈ "	0.40 lbs	50
UG-TR/D1/240	Digital Timer 240V, Single outlet	240	15	60	3500	2 ⁷ / ₈ "	3 ¹ / ₂ "	4 ⁵ / ₈ "	0.40 lbs	50
UG-TR/D2/120	Digital Timer 120V, Dual outlets	115	15	60	1725	3"	3 ¹ / ₂ "	3"	0.45 lbs	40



UL US LISTED
UG-TR/M1/120



UG-TR/M1/240



UL US LISTED
UG-TR/M2/120



ETL Intertek 3172645
UG-TR/M8/120

Mechanical Timers: 1 Year Warranty

Item Code	Description	Volts	Amps	Hz	Watts	Length	Width	Height	Weight	CS/QTY
UG-TR/M1/120	Mechanical Timer 120V, Single outlet	115	15	60	1725	2 ⁷ / ₈ "	3 ¹ / ₂ "	4 ⁵ / ₈ "	0.40 lbs	50
UG-TR/M1/240	Mechanical Timer 240V, Single outlet	240	15	60	3500	2 ⁷ / ₈ "	3 ¹ / ₂ "	4 ⁵ / ₈ "	0.40 lbs	50
UG-TR/M2/120	Mechanical Timer 120V, Dual outlets	115	15	60	1725	3"	3 ¹ / ₄ "	3"	0.45 lbs	40
UG-TR/M8/120	Power Strip w/ Timer (8 Outlets)	125	15	60	1725	11 ¹ / ₂ "	1"	3 ¹ / ₄ "	1 lbs	20

Hydrometer & Power Strip: 1 Year Warranty

Item Code	Description	Length	Width	Height	Weight	CS/QTY
UG-MISC/TCH	Temperature/Clock/Humidity	3 ³ / ₄ "	5 ⁸ / ₈ "	4 ¹ / ₈ "	0.40 lbs	50



Temperature Measurement Range:

Indoor: 0 °C ~ 50 °C (32 °F ~ 122 °F)

Outdoor: -50 °C ~ 70 °C (-58 °F ~ -158 °F)

Humidity: 10-99%

Accuracy: Temperature: ± 1 °C (15 ~ 35 °C)

Humidity: ± 5% (40 ~ 80%)

Other: ± 2 °C Other: ± 8%

Resolution: temperature: 0.1 °C. Humidity 1%.