

Project \_\_\_\_\_  
 Schedule \_\_\_\_\_ Date \_\_\_\_\_  
 Notes \_\_\_\_\_

**DESCRIPTION**

naturaLED<sup>®</sup> PAR and MR LED bulb provides a superior replacement for all incandescent PAR and MR lamp applications. An energy efficient integrated LED driver deliver the same lumen output equivalent with up to 85% energy savings. Our LEDs are direct replacement with energy star certification.

Perfect for display case lighting, track lighting, jewelry lighting and general lighting.



**FEATURES**

- Energy Star Certified
- Direct replacement and Instant On
- Up to 85% energy savings
- Uniform and consistent color
- Contains no mercury or lead
- UL/cUL Listed
- Input line voltage: 120V / 12V
- Operating temperature: -22°F ~ 122°F
- Beam Angle: 30°/40°
- Noise-free design
- Rated 25,000 hours average life

**APPLICATIONS**

- Display Case Lighting
- Track Lighting
- Recessed Downlight
- Accent Lighting
- General Lighting

**WARRANTY**







- 3 Year Warranty

Ordering Information		EXAMPLE: LED15PAR38/OD/120L/FL/930				
LED	15	PAR38	OD	120L	FL	930
	<b>Wattage</b>	<b>Style</b>	<b>Style</b>	<b>Lumens</b>	<b>Beam Angle</b>	<b>Color Temp/CRI</b>
<b>LED</b>	<b>15</b> 15-Watts	<b>PAR38</b> PAR38	<b>OD</b> Outdoor	<b>120L</b> 1,200 lm	<b>FL</b> Flood	<b>9</b> CRI90 <b>30</b> 3000K <b>40</b> 4000K <b>50</b> 5000K

ORDERING

Watts (W)	Ordering Code	Description	Color Temp (K)	Lumens (lm)	Equiv. Wattage (W)	Base	CRI	Beam Angle	Rated Hrs	Wet Location	Energy Star
8	5924	LED8PAR20/50L/FL/930	3000K	500	50	E26	90	40°	25,000		•
8	5925	LED8PAR20/50L/FL/950	5000K	500	50	E26	90	40°	25,000		•
10	5926	LED10PAR30/80L/FL/930	3000K	800	75	E26	90	40°	25,000		•
10	5927	LED10PAR30/80L/FL/950	5000K	800	75	E26	90	40°	25,000		•
10	5928	LED10PAR30L/OD/80L/FL/930	3000K	800	75	E26	90	40°	25,000	•	•
10	5906	LED10PAR30L/90L/930	3000K	900	75	E26	90	40°	25,000	•	•
10	5929	LED10PAR30L/OD/80L/FL/950	5000K	800	75	E26	90	40°	25,000	•	•
15	5930	LED15PAR38/OD/120L/FL/930	3000K	1,200	90	E26	90	40°	25,000	•	•
15	5998	LED15PAR38/OD/120L/FL/940	4000K	1,200	90	E26	90	40°	25,000	•	•
15	5931	LED15PAR38/OD/120L/FL/950	5000K	1,200	90	E26	90	40°	25,000	•	•
6	4565	LED6MR16/50L/FL/830 (12V)	3000K	500	50	GU5.3	80	40°	25,000	Damp	•
6.5	4566	LED6.5MR16/50L/GU10/FL/930 (120V)	3000K	500	50	GU10	90	40°	25,000	Damp	•
7	5999	LED7MR16/50L/FL/850 (12V)	5000K	500	50	GU5.3	80	40°	25,000	Damp	•
7	5939	LED7MR16/50L/GU10/FL/850 (120V)	5000K	500	50	GU10	80	40°	25,000	Damp	•

## SPECIFICATIONS

<p><b>PAR 20</b>    Weight: 3.68-oz</p> 	<p><b>PAR 30</b>    Weight: 6.56-oz</p> 	<p><b>PAR 30L</b>    Weight: 7.68-oz</p> 
<p><b>PAR 38</b>    Weight: 12.64-oz</p> 	<p><b>MR16 -7W</b>    Weight: 1.76-oz</p> 	<p><b>MR16- GU10</b>    Weight: 1.76-oz</p> 

## PACKAGE

