

(FMC) Contemporary Flush Mount Ceiling Light

- ▶ Available in 12" or 14" diameters
- ▶ Contemporary, elegant two ring design
- ▶ 2.5" low profile "Driver-On-Board" LED technology
- ▶ Backlit design with UV-resistant PC diffuser for uniform lighting, excellent light transmittance and colour consistency
- ▶ Available in brushed nickel finish
- ▶ Aluminum design for efficient heat dissipation
- ▶ Easily mounts to standard fire-rated junction boxes
- ▶ Flicker free driver
- ▶ 5CCT Selectable: 2700K-3000K-3500K-4000K-5000K
- ▶ CRI Ra80+
- ▶ Suitable for dry or damp locations
- ▶ Recommended ceiling height: 8-10ft
- ▶ Suitable for residential or commercial applications
- ▶ Input line voltage: 120Vac; 50/60Hz
- ▶ TRIAC dimming
- ▶ Suitable for retrofit or new installation
- ▶ LM80 25,000 hour average life
- ▶ Operating temperature: -20°C to 40°C
- ▶ 5 Year Limited Warranty



Performance

| Model Number | Diameter | CCT Selectable | Wattage Setting | Beam Angle | Lumens |
|--------------------------------|----------|----------------|-----------------|------------|---------|
| LEDI-PR305M-CL02-20W120-5CCT/S | 12" | 5CCT | 20W | Flood 120° | 1,400lm |
| LEDI-PR355M-CL02-26W120-5CCT/S | 14" | 5CCT | 26W | Flood 120° | 1,820lm |

Dimensions

