

(PVDL) Backlit Slim Down Light with Baffle Trim

- ▶ Available in 4" and 6" dimensions
- ▶ Modern, low profile, backlit design
- ▶ High luminous efficacy: 110lm/W
- ▶ Baffle trim softens the intensity of the light source
- ▶ Regressed light source, low glare design UGR <18
- ▶ Air tight and IC rated
- ▶ Commercial grade 1.25" torsion spring clips
- ▶ FT6/CMP Plenum rated cables
- ▶ Junction box with easy wiring access for quick installation
- ▶ Flicker free driver
- ▶ Selectable 5CCT: 2700K-3000K-3500K-4000K-5000K
- ▶ Acrylic diffuser designed for uniform lighting, excellent light transmittance and colour consistency
- ▶ Suitable for dry or damp locations
- ▶ Recommended ceiling height: 8-10ft
- ▶ Suitable for residential or commercial applications
- ▶ Input line voltage: 120VAC; 50/60Hz
- ▶ TRIAC dimming
- ▶ CRI Ra80+
- ▶ Suitable for retrofit or new installation
- ▶ LM70 25,000 hour average life
- ▶ Operating temperature: -40°C to 40°C
- ▶ 5 Year Limited Warranty



Performance

Model Number	Diameter	CCT Selectable	Wattage Setting	Beam Angle	Lumens
PVDL-GEN02-8WE-01 122955	4"	5CCT	8W	Flood 108°	880lm
PVDL-GEN02-12WG-01 122956	6"	5CCT	12W	Flood 108°	1,320lm

Dimensions

