

LED Reflector Lamps

PAR20, PAR30SN, PAR30, PAR38, MR16

- Direct replacement for traditional incandescent reflector lamps
- Precise light distribution and consistent colour
- Suitable for residential or commercial applications
- Dimmable, instant on
- CCT: 3000K, 4000K, 5000K CRI: Ra80
- Energy Star
- UL Wet/Damp Location
- Beam Angle: 40° / 35°
- PAR Input Voltage: 120V
- MR16 Input Voltage: 12V
- Operating temperature: -20°C~40°C
- 3 Year Warranty



MODEL	Input Voltage (V)	Base	Wattage (W)	Lumen Output (lm)	Beam Angle	CCT (K)	Dimmable	CRI	Life Time (Hrs)	Power Factor	Wet Rated	Energy Star	Case Quantity	Warranty
MR16 DIMMABLE ENERGY STAR Gu5.3														
LEDI-G6 TP12- 6.5/ MR16 DIM VE 3000K	12	Gu5.3	6.5	500 ±10%	35°	3000	YES	≥80	25000	>0.9	NO	YES	100	3 Years
LEDI-G6 TP12- 6.5/ MR16 DIM VE 4000K	12	Gu5.3	6.5	500 ±10%	35°	4000	YES	≥80	25000	>0.9	NO	YES	100	3 Years
PAR20 DIMMABLE ENERGY STAR														
LEDI-G8 TP120- 5/ PAR20 DIM 3000K	120	E26	5	500 ±10%	40°	3000	YES	≥80	15000	>0.7	YES	YES	50	3 Years
LEDI-G8 TP120- 5/ PAR20 DIM 4000K	120	E26	5	500 ±10%	40°	4000	YES	≥80	15000	>0.7	YES	YES	50	3 Years
LEDI-G8 TP120- 5/ PAR20 DIM 5000K	120	E26	5	500 ±10%	40°	5000	YES	≥80	15000	>0.7	YES	YES	50	3 Years
PAR30 SHORT NECK DIMMABLE ENERGY STAR E26														
LEDI-G8 TP120- 8/ PAR30S DIM 3000K	120	E26	8	800 ±10%	40°	3000	YES	≥80	15000	>0.7	YES	YES	50	3 Years
LEDI-G8 TP120- 8/ PAR30S DIM 4000K	120	E26	8	800 ±10%	40°	4000	YES	≥80	15000	>0.7	YES	YES	50	3 Years
LEDI-G8 TP120- 8/ PAR30S DIM 5000K	120	E26	8	800 ±10%	40°	5000	YES	≥80	15000	>0.7	YES	YES	50	3 Years



LED Reflector Lamps

PAR20, PAR30SN, PAR30, PAR38, MR16

- Direct replacement for traditional incandescent reflector lamps
- Precise light distribution and consistent colour
- Suitable for residential or commercial applications
- Dimmable, instant on
- CCT: 3000K, 4000K, 5000K CRI: Ra80
- Energy Star
- UL Wet/Damp Location
- Beam Angle: 40° / 35°
- PAR Input Voltage: 120V
- MR16 Input Voltage: 12V
- Operating temperature: -20°C~40°C
- 3 Year Warranty



MODEL	Input Voltage (V)	Base	Wattage (W)	Lumen Output (lm)	Beam Angle	CCT (K)	Dimmable	CRI	Life Time (Hrs)	Power Factor	Wet Rated	Energy Star	Case Quantity	Warranty
PAR30 DIMMABLE ENERGY STAR E26														
LEDI-G8 TP120- 8/ PAR30L DIM 3000K	120	E26	8	800 ±10%	40°	3000	YES	≥80	15000	>0.7	YES	YES	50	3 Years
LEDI-G8 TP120- 8/ PAR30L DIM 4000K	120	E26	8	800 ±10%	40°	4000	YES	≥80	15000	>0.7	YES	YES	50	3 Years
LEDI-G8 TP120- 8/ PAR30L DIM 5000K	120	E26	8	800 ±10%	40°	5000	YES	≥80	15000	>0.7	YES	YES	50	3 Years
PAR38 DIMMABLE ENERGY STAR E26														
LEDI-G8 TP120- 12.5/PAR38 DIM 3000K	120	E26	12.5	1200 ±10%	40°	3000	YES	≥80	15000	>0.7	YES	YES	20	3 Years
LEDI-G8 TP120- 12.5/PAR38 DIM 4000K	120	E26	12.5	1200 ±10%	40°	4000	YES	≥80	15000	>0.7	YES	YES	20	3 Years
LEDI-G8 TP120- 12.5/PAR38 DIM 5000K	120	E26	12.5	1200 ±10%	40°	5000	YES	≥80	15000	>0.7	YES	YES	20	3 Years

